

APX™ 7000

Project 25 Multi-Band Portable Radio



Top Display Model:

- Up to 96 channels
- Universal Push-to-Talk
- T-Grip
- Dual Battery Latch
- Orange emergency button
- 16 position rotary knob
- 2 position concentric switch
- 3 position toggle switch
- 3 programmable side buttons
- Transmit LED indicator
- Full Bitmap Top Display
 - 1 line of icons
 - 1 line x 8 characters of text
- No keypad



Dual Display Model:

- Same as APX Top Display model plus the following features:
- 1250 channels
- Dial from pre-stored lists or free-form entry
- Programmable soft keys for easy access to radio menus
- Backlit Keypad
 - Home and Data buttons
 - 3 soft keys
 - 4 direction navigation key
 - 4 x 3 keypad
- Full Bitmap Display
 - 2 lines of icons
 - 4 lines x 14 characters of text
 - Status icons

The APX 7000 Multi-Band P25 Portable Radio delivers exceptional performance combining advanced voice and data technology driven by the challenges of mission critical users.

Motorola's 4th generation P25 subscriber is multi-band (700/800 MHz and VHF), communicates with current and future networks (FDMA and TDMA) and has integrated GPS. Designed specifically for first responders the dual-sided mission critical design has both an audio and data side providing optimal functionality and loud and clear audio in a compact rugged form factor.

DATA SHEET

APX 7000
Project 25 Multi-Band Portable Radio

FEATURES AND BENEFITS:

Available in 700/800 MHz and VHF bands

Optional multi-band operation

Trunking standards supported:

- Clear or digital encrypted ASTRO®25 Trunked Operation
- Capable of SmartZone®, SmartZone Omnilink, SmartNet®

Analog MDC-1200 and Digital APCO P25 Conventional System Configurations

Narrow and wide bandwidth digital receiver
(6.25kHz / 12.5 kHz / 25 kHz)

Embedded digital signaling (ASTRO & ASTRO 25)

Integrated GPS capable

Seamless wideband scan

Intelligent Lighting

Radio Profiles

Unified Call List (Dual Display model only)

Expansion Slot

Standard 64 MB internal memory

Micro SD removable memory card

Meets Applicable Mil Specs 810C, D, E and F

Ships standard IP67 (1 meter, 30 minutes)

Ruggedized housing option available

Custom recessed label areas

Superior Audio Features:

- 1W high audio speaker
- Dual speakers (Dual Display model only)
- Dual microphones
- 2-mic noise canceling technology

Utilizes Windows XP and Vista Customer Programming Software (CPS)

- Supports USB communications
- Built in FLASHport™ support

OPTIONAL FEATURES:

Enhanced Encryption capability

Programming Over Project 25

Over the Air Rekey

Text Messaging

TRANSMITTER – TYPICAL PERFORMANCE SPECIFICATIONS

	700MHz	800MHz	VHF
Frequency Range/Bandsplits	764-776 794-806	806-825 851-870	136-174
Channel Spacing	25/20/12.5 KHz	25/20/12.5 KHz	25/20/12.5 KHz
Maximum Frequency Separation	Full Bandsplit	Full Bandsplit	Full Bandsplit
Rated RF Output Power Adj*	1-3 Watts Max	1-3 Watts	1-6 Watts
Frequency Stability* (-30°C to +60°C; +25°C Ref.)	±0.000020 %	±0.000030 %	±0.000025 %
Modulation Limiting*	5 kHz / 4 kHz / 2.5 kHz	5 kHz / 4 kHz / 2.5 kHz	5 kHz / 4 kHz / 2.5 kHz
Emissions (Conducted and Radiated)*	-75 dB	-75 dB	-75dB
Audio Response*	+1, -3 dB	+1, -3 dB	+1, -3 dB
FM Hum & Noise	-48 dB	-47 dB	-47 dB
Audio Distortion*	0.60%	1%	0.50%

BATTERIES FOR APX 7000

Battery Capacity /Type	Dimensions (HxWxD)	Weight	Battery Part Numbers	Battery Capacity
Li-Ion IMPRES 2900 mAh (Standard)	3.07" x 2.34" x 1.65"	6.53 oz	NNTN7038A	2900 mAh
NiMH IMPRES 2100 mAh IP67	5.07" x 2.34" x 1.57"	11.82 oz	NNTN7037A	2100 mAh
NiMH IMPRES 2000 mAh FM IP67	5.07" x 2.34" x 1.57"	11.82 oz	NNTN7036A	2000 mAh
NiMH IMPRES 2000 mAh FM Delta-T	5.07" x 2.34" x 1.57"	11.82 oz	NNTN7035A	2000 mAh
NiMH IMPRES 2100 mAh Delta-T (Non-FM)	5.07" x 2.34" x 1.57"	11.82 oz	NNTN7573A	2100 mAh

DATA SHEET

APX 7000
Project 25 Multi-Band Portable Radio

RECEIVER – TYPICAL PERFORMANCE SPECIFICATIONS

	700MHz	800MHz	VHF
Frequency Range/Bandsplits	764-776	851-870	136-174 MHz
Channel Spacing	12.5/25 kHz	12.5/25 kHz	12.5/25 kHz
Maximum Frequency Separation	Full Bandsplit	Full Bandsplit	Full Bandsplit
Audio Output Power at Rated*	1000mW	1000mW	1000mW
Frequency Stability* (-30°C to +60°C; +25°C Ref.)	±0.000080 %	±0.000080 %	±0.000086 %
Analog Sensitivity** 12 dB SINAD	0.250 µV	0.250 µV	0.216 µV
Digital Sensitivity+ 1% BER	0.347 µV	0.333 µV	0.277 µV
5% BER	0.251 µV	0.251 µV	0.188 µV
Selectivity* 25 kHz channel	75.7 dB	75.7 dB	79.3 dB
12.5 kHz channel	67.5 dB	67.5 dB	70 dB
Intermodulation	80 dB	80 dB	80.5 dB
Spurious Rejection	76.6 dB	76.6 dB	93.2 dB
FM Hum and Noise 25 kHz	-54 dB	-54 dB	-53.8 dB
12.5 kHz	-48 dB	-48 dB	-48 dB
Audio Distortion*	1.60%	1.60%	1.30%

RADIO MODELS

	Display	Keypad	Channel Capacity	FLASHport Memory	700/800 MHz (764-870 MHz)	VHF (136-174 MHz)	Buttons/Switches	Embedded GPS	LED
Top Display	Full bitmap monochromatic LCD display 1 line text x 8 characters 1 line of icons No menu support Multi-color backlight	None	96 (using zone bank feature)	64 MB	H97TGD9PW1_N QA00569	H97TGD9PW1_N QA00570	Large PTT button Angled On/Off Volume knob Orange emergency button 16-position top-mounted rotary knob 2-position concentric switch 3-position toggle switch 3 programmable side buttons	Yes	Multi-color
Dual Display	Top display + Full bitmap color LCD display: 4 lines text x 14 characters 2 lines of icons 1 menu line x 3 menus White backlight	Multi-color backlight Keypad 3 soft keys 4-direction navigation key 4x3 keypad Home and Data buttons	1250	64 MB	H97TGD9PW1_N QA00569 QA00577	H97TGD9PW1_N QA00570 QA00577	Large PTT button Angled On/Off Volume knob Orange emergency button 16-position top-mounted rotary knob 2-position concentric switch 3-position toggle switch 3 programmable side buttons	Yes	Multi-color
Transmitter Certification					AZ489FT7036	AZ489FT7036			
FCC Emissions Designators	11K0F3E, 16K0F3E, 8K10F1D, 8K10F1E, 8K10F1W, 20K0F1E								
Power Supply	One rechargeable Li-Ion 2900 mAh battery, or one optional NiMH								

DIMENSIONS OF THE RADIOS WITHOUT BATTERY

	Inches	Millimeters
Length	6.29	159.71
Width Push-to-Talk button	2.31	58.69
Depth Push-to-Talk button	1.34	34
Width Top	2.98	75.69
Depth Top	1.6	40.52
Depth Bottom of Battery	1.65	41.78
Weight of the radios without battery	12.2 oz	

DATA SHEET

APX 7000
Project 25 Multi-Band Portable Radio

PORTABLE MILITARY STANDARDS 810 C, D, E & F

	MIL-STD 810C		MIL-STD 810D		MIL-STD 810E		MIL-STD 810F	
	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II
High temperature	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Hot
Low Temperature	502.1	I	502.2	I/C3, II/C1	502.3	I/C3, II/C1	502.4	I/C3, II/C1
Temperature Shock	503.1	-	503.2	I/A1C3	503.3	I/A1C3	503.4	I
Solar Radiation	505.1	II	505.2	I	505.3	I	505.4	I
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, II
Humidity	507.1	II	507.2	II	507.3	II	507.4	-
Salt Fog	509.1	-	509.2	-	509.3	-	509.4	-
Blowing Dust	510.1	I	510.2	I, II	510.3	I, II	510.4	I, II
Immersion**	512.1	I	512.2	I	512.3	I	512.4	I
Vibration	514.1	VIII/F, Curve-W	514.3	I/10, II/3	514.4	I/10, II/3	514.5	I/24
Mechanical Shock	516.1	I, II	516.3	I, IV	516.4	I/IV	516.5	I, IV

ENCRYPTION

Supported Encryption Algorithms	ADP, AES, DES, DES-XL, DES-OFB, DVP-XL
Encryption Algorithm Capacity	8
Encryption Keys per Radio	Module capable of storing 1024 keys. Programmable for 64 Common Key Reference (CKR) or 16 Physical Identifier (PID)
Encryption Frame Re-sync Interval	P25 CAI 300 mSec
Encryption Keying	Key Loader
Synchronization	XL – Counter Addressing OFB – Output Feedback
Vector Generator	National Institute of Standards and Technology (NIST) approved random number generator
Encryption Type	Digital
Key Storage	Tamper protected volatile or non-volatile memory
Key Erasure	Keyboard command and tamper detection
Standards	FIPS 140-3 FIPS 197

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-30° C / +60° C
Storage Temperature	-40° C / +85° C
Humidity	Per MIL-STD
ESD	IEC 801-2 KV
Water & Dust Intrusion	IP67 MIL-STD

RUGGED OPTION SPECIFICATIONS

Leakage (immersion)**	MIL-STD-810 C, D, E, F Method 512.X Procedure I
-----------------------	--

* Measured in the analog mode per TIA / EIA 603 under nominal conditions
 ** Measured conductively in analog mode per TIA / EIA 603 under nominal conditions
 + Measured conductively in digital mode per TIA / EIA IS 102.CAAA under nominal conditions
 ** For rugged models only

Specifications subject to change without notice. All specifications shown are typical.
 Radio meets applicable regulatory requirements.



Motorola, Inc. 1301 E. Algonquin Road, Schaumburg, Illinois 60196 U.S.A. www.motorola.com/governmentandenterprise 1-800-367-2346

MOTOROLA and the Stylized M Logo are registered in the U.S. Patent and Trademark Office.
 All other product or service names are the property of their registered owners. © Motorola, Inc. 2009 (0905)
 R3-4-2021